



RING SIZE CHART

US/Canada Number Size	Inside Diameter (ID) Inches	Inside Diameter (ID) Closest Fraction		Inside Diameter (ID) Millimeters	Recommended Wood Blank ID *	Recommended Wood Blank ID *
		FRACTION	DECIMAL		Millimeters	Inches
3	0.554	9/16	= 0.563	14.07	15.21	0.599
3½	0.57			14.48	15.62	0.615
4	0.586	19/32	= 0.594	14.88	16.03	0.631
4½	0.602			15.29	16.43	0.647
5	0.618	5/8	= 0.625	15.70	16.84	0.663
5½	0.634			16.10	17.25	0.679
6	0.65	21/32	= 0.656	16.51	17.65	0.695
6½	0.666			16.92	18.06	0.711
7	0.682	11/16	= 0.688	17.32	18.47	0.727
7½	0.698			17.73	18.87	0.743
8	0.714	23/32	= 0.719	18.14	19.28	0.759
8½	0.73			18.54	19.69	0.775
9	0.746	3/4	= 0.750	18.95	20.09	0.791
9½	0.762			19.35	20.50	0.807
10	0.778	25/32	= 0.781	19.76	20.90	0.823
10½	0.794			20.17	21.31	0.839
11	0.81	13/16	= 0.813	20.57	21.72	0.855
11½	0.826			20.98	22.12	0.871
12	0.842	27/32	= 0.844	21.39	22.53	0.887
12½	0.858			21.79	22.94	0.903
13	0.874	7/8	= 0.874	22.20	23.34	0.919
13½	0.89			22.61	23.75	0.935
14	0.906	29/32	= 0.906	23.01	24.16	0.951
14½	0.922			23.42	24.56	0.967
15	0.938	15/16	= 0.938	23.83	24.97	0.983

* The recommended wood blank ID is for use with WildWood Design Two-Piece Ring Cores.
The suggested wood to metal clearance is 0.005", preferably with a flexible adhesive for bonding.